

**WATCH THE
VIDEO!**




NOTIF EYE™

POWERED BY TEMPTRAK

Cloud-based Monitoring
and Notification System



#15501
Ethernet Gateway
(Kit #15901)



#15500
USB Gateway
(Kit #15900)

WIRELESS SENSORS MONITOR INVENTORY ENVIRONMENT CONDITIONS,
DETECT INCIDENTS AND SEND DATA VIA GATEWAYS TO THE
NOTIFEYE™ SYSTEM



#15502
Repeater
Extends Sensor Range
(Optional)



#15100
Temperature Sensors (4 per kit)



#15502
Repeater
Extends Sensor Range
(Optional)

The NotifEye™ cloud-based temperature monitoring and notification system is a low-cost wireless solution that is self-installable and ready to use out-of-the-box.

Let NotifEye™ keep an eye on your valuable perishable inventory and save you time documenting temperatures.

View the NotifEye™ Online System and Live Data!

Log into www.notifeyewireless.com – User Name: demo / Password: demo2013



Accuracy to the Highest Degree

Cooper-Atkins Corporation • 800-835-5011 • 860-347-2256 • www.cooper-atkins.com



Cloud-based Monitoring
and Notification System

Highly Accurate
Temperature Air Probe
(with 3 ft lead)

Flexible Antenna
(250-300 ft Range)

Sensors Can Be Secured
with Provided Screws
or Loop & Lock Tape

900 or 868 MHz
Operating Frequency

Long-life Lithium Ion Battery

Robust ABS Plastic
Housing

#15100 Temperature Sensor Specifications	#15120 Humidity Sensor Specifications
Temperature Range: -40° to 257°F (-40° to 125°C)	Relative Humidity Range: 0-100% RH
Accuracy: $\pm 1.8^{\circ}\text{F}$ ($\pm 1^{\circ}\text{C}$)	Accuracy: $\pm 2\%$ under normal conditions (50-90% RH)
<i>Additional sensors, gateways and repeaters to expand your system are sold separately</i>	
Ambient Operating Range: 20° to 140°F (-7° to 60°C)	
Communication: RF 900 MHz or 868 MHz (CE Certified). Antenna: 4" high-gain flexible antenna	
Sensor Range: 250-300 ft non-line-of-sight (actual range may vary depending on environment)	
Power: Replaceable 3.0 V Lithium coin cell battery	
Battery Life: 2-3 years at 2-hour heartbeat (battery life determined by sensor reporting frequency and other variables)	
1-year warranty	
#15502 Repeater	
Extends the signal range between sensors and gateways	
Supports up to 100 sensors	

SENSOR FEATURES:

- Basic Sensor Configurations (Name Sensor, Set Heartbeat, Select Unit of Measurement)
- Advanced Sensor Configurations (Recovery Attempts, Inactivity Alerts, Sub Heartbeat Assessments)
- Sensor Configuration by Group
- Sensor Grouping by Gateway, Type or Status
- Unlimited Number of Networks, Sensors, Gateways and Users Supported
- Sensor Mapping Tool (Visual Placement)
- Sensor Data Reports and History Storage
- Visual Charts and Exports
- Sensor Readings are Buffered if Internet Connection is Lost
- Extend the sensor range up to 50% by including a Repeater (#15502)

ALERT FEATURES:

- On-screen Alerts and Notifications (Single User or Multiple Recipients)
- Notifications via Email and SMS Text
- Permission-based Access Control and Reporting
- List of Recent Alerts for Individual Sensors

NotifEye sensors relay data every 2 hours (when set to the recommended 2-hour heartbeat). If preset limits are exceeded an alert notification is sent immediately and does not wait for the next heartbeat.

#15501 Ethernet Gateway Minimum System Requirements	#15500 USB Gateway Minimum System Requirements
<ul style="list-style-type: none"> • Internet Access via Ethernet Port • PC / MAC Compatible • 110 V (USA) or 220 V (Europe) 	<ul style="list-style-type: none"> • An Available USB Port • Windows 8, 7 and Vista • 10 MB Free Disk Space • ASP.NET 3.5 • Computer Must be Left ON for Data Transfer to Occur <p><i>*Not Windows XP or MAC Compatible</i></p>



Accuracy to the Highest Degree
Cooper-Atkins Corporation • 800-835-5011 • 860-347-2256 • www.cooper-atkins.com

67-1339
V1113